



# HI-TEMP ACCESS DOORS

Provides easy access into grease duct or high-temp duct systems

Model No.  
**ACC-12X8**

Model No.  
**ACC-10X6-6**  
6" mounting studs

Model No.  
**ACC-10X6**



### ACCESS DOORS WITH 6" MOUNTING STUDS For Applications Using Fire Wrap Insulation

MODEL NO.	DIMENSIONS	CASE QTY
ACC-10X6-6	10" x 6" (254mm x 152mm)	6
ACC-12X8-6	12" x 8" (305mm x 203mm)	6

### ACCESS DOORS

MODEL NO.	DIMENSIONS	CASE QTY
ACC-10X6	10" x 6" (254mm x 152mm)	10
ACC-12X8	12" x 8" (305mm x 203mm)	10
ACC-18X14	18" x 14" (457mm x 356mm)	4

- HI-TEMP ACCESS DOOR IS SOLID, LEAK RESISTANT AND CONSISTS OF TWO LAYERS OF STAMPED, HOT DIPPED GALVANIZED STEEL AND ONE 16 GAUGE BLACK IRON BACKING PLATE
- HI-TEMPERATURE CERAMIC FIBER GASKET (2300°F, 1260°C MAX-MEETS NFPA 96 STANDARDS) IS PERMANENTLY BONDED TO THE OUTSIDE PANEL OF THE ACCESS DOOR TO ELIMINATE LEAKAGE
- ZINC PLATED CONICAL SPRINGS ARE INSTALLED, BETWEEN THE INNER AND OUTER PLATES, TO FACILITATE OPENING
- ZINC COATED WING NUTS ARE EASILY TURNED BY HAND
- NO MEASURING (SELF-ADHESIVE TEMPLATE PROVIDED)

## Easy to Install



1. Peel backing off tem-plate and apply to duct in desired location.
2. Opening can be cut with hand-held plasma cutter or by conventional methods.
3. Insert door into opening at an angle and tighten knobs.
4. Do not overtighten knobs or wing nuts.

